



SERIES 2072

DISPERSER, POST MOUNTED, VARIABLE HIGH SPEED VECTOR DRIVE

MODEL DVF-250-52/30-TEFC/SS

Features:

- Motor: 25 HP, 1750 rpm, 3-phase, 60 Hz, 460V, Inverter Duty, 20: 1, 284T, TEFC
- Mixing Shaft Speed Range: 300 to 3000 rpm
- Mixing shaft diameter is 2 1/4" SS304
- Air-Over-Oil Lift, 52" rise, with controls
- Lift limit switch
- High Speed Blade, HSF, 14"
- Controller, NEMA 1, Vector Drive, 3/60/460V input power

This Disperser is designed with a variable speed, pulleys, belt, inverter duty motor drive, The motor is electrically connected to the Vector Drive Controller resulting in precise speed control with significant energy savings.

The Controller is programmed at the factory to be turned on/off, to display rpm and to operate (run up or down) within the specified speed range. Interconnection will be done by the customer at site. The unit has to be electrically protected as directed by local code.

The Controller in NEMA 1 enclosure is shown mounted on a pedestal (pedestal is optional). The controller may be mounted on the wall by the Disperser and must be protected from liquid or water sprays.

If wash down of the equipment is part of the process, then the Controller has to be moved away from the Disperser in a safe area. In this case the Disperser has to be controlled by an industrial type control box (Model RCB-VFI-N12-T) in NEMA 12 enclosure with digital tachometer, digital ammeter, speed pot and E-stop. This box is humidity proof and it may be located by the Disperser mounted on a wall or on a pedestal. This box may be quoted on demand.

The lift limit switch is wired at site to shut down the motor when the lift is raised while the motor is energized.



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>