



**SERIES 5016  
PORTABLE MIXER, FIXED MOUNT,  
FIXED LOW SPEED**

MODEL DTE-100-350/60-2/12-EX/SS

Application: mixing fragrance oil and other chemicals or coatings.

STANDARD FEATURES:

- 1 HP motor, expl. proof, 1750 rpm, 3/60/230/460V
- reducer, in line, flanged
- mixing shaft speed 350 rpm
- mixing shaft diameter 7/8", 60" long
- mid turbine, 12" diameter, type AFF, 4 pitched blades, 1/4" x 2", axial flow down
- bottom turbine, 14" diameter, type VHE-S, 3 pitched blades, 1/4" x 2", stabilizer, axial flow down
- rigid sleeve coupling, keyed
- tank side mounted adapter plate
- wetted parts, stainless steel, type 304
- weight, 75 lbs

Various turbine designs are available, i.e. axial flow (AFF), radial flow (RAF), high efficiency (VHE), butterfly (DEF), helical (RB-1FD), gate (GB), etc



DANTCO MIXERS CORPORATION  
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL [sales@dantco.com](mailto:sales@dantco.com), WEB <http://www.dantco.com>