



**REACTOR, SANITARY FINISH,
VACUUM/PRESSURE, F&D BOTTOM &
TOP, HEATING JACKET 75 PSIG & 350
DEGREES F, VARIABLE LOW SPEED
AGITATOR, HIGH EFFICIENCY
BOTTOM TURBINE**

PROCESSING: GELS, CREAMS, PASTES

MODEL DSL-150-78/400-2C-EXSS

- 200 gallon working capacity, 230 gal. Max.
- sanitary polish, 240 grits
- hot oil heating jacket, 75 psig
- 20" manway, Viton seal
- glass viewport
- sight glass light, EX, 120V
- 2" insulation, rated 1200 degrees F
- insulation skin, sealed, welded, & polished
- inside coating "Plasmadized", .002" min.
- 15 HP agitator, variable speed, 80 to 400 rpm, explosion proof, vacuum seal
- 4 pitched blades mid turbine, axial flow
- very high efficiency bottom turbine
- SS 316 vessel & wetted parts

APPLICATIONS:

- High viscosity, high vacuum mixing of viscoelastic materials process system (gels).
- Cosmetics creams & pastes.
- Adhesives



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>