



SERIES 5065

VERTICAL RIBBON BLENDER, SINGLE RIBBON ELECTRIC MOTOR WITH VFD DRIVE VARIABLE LOW SPEED

MODEL VRB-SRI-CB-02-30/40-SS304

Features:

- Motor, 2 HP, 1750 rpm, 3-phase, 60 Hz, 230/460V, 145 TC, Inverter Duty, 10:1 ratio, explosion proof, Class 1, Group D
- Gear Reducer, SEW, Flange Mounted, Hollow Shaft, 39:1 ratio, Output Speed 43 rpm @ 1750 motor rpm With VFD speed range is 10 to 50 rpm
- Bearing Housing, with Stabilizer Bearing, High Temperature Packing Seal, Garlock Style 98, and Mounting Flange, 2" ANSI Standard, SS 304
- Mixing Shaft, Ground & Polished, 1 1/4" SS304
- Ribbon Impeller, single ribbon, type SRI-CB-30/40-SS304, 30" diameter, with 1 1/2" wide ribbon, 1" rods, pinned, rigid coupling, all in SS304, sanitary polish
- Clearance between ribbon and cone bottom tank shell is about 1/2"
- Flow direction, axial, upward against gravity
- Statically balanced

Cone Bottom Tank, 40" deep, Dome Top with 2" ANSI mixer Mounting Flange, VFD drive, remote control box, explosion proof, (not shown)



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>