



PORTABLE MIXING TANK

Lift Tubes, 15 psig jacket

MODEL PTA-LTJ-350-SS-SB

Features:

- Capacity, max. 350 gal
- Materials: Stainless Steel, type 304
- Lift tubes, 7" x 3" on 28" center
- Sloping bottom, 4"
- Ball valve, drain: 2"
- Diameter: 50"
- Straight section: 42"
- OAH: 47"
- Top ring, angle: 2"x2"x1/4"
- Shell thickness, outer: 12 ga
- Shell thickness, inner: 10 ga
- Bottom thickness: 10 ga.
- Jacket with spirals: 15 psig
- Inside welds, ground smooth
- Outside 2" insulation, 900 degrees F, fabric & white cement coating, (not shown)
- Product viscosity: 10k cps
- Heavy duty construction

Options:

- Valve guard, 10 ga., SS304
- Mixer, Series 5016, Model DTE-020-380-SS, tank mounted, fixed speed 380 rpm, 2 HP TEFC gear motor, 3/60/460V, 12" turbine type VHE
- Lid, 1" lip ring, hinged one side, mixer entry slot, SS304
- Choice of materials



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>