



PAIL/KETTLE, SANITARY, CONE BOTTOM, 75 PSIG HEATING/COOLING JACKET,

Standard Specifications:

- Jacket pressure: 75 psig
- Jacket inlet/outlet: 3/8" FNPT
- Cover, split:
- Bottom cone depth: 2 1/2" to 3"
- Drain, ferrule:
- Materials: SS304
- Finish, inside: 240 grit

Left to right:

Model TFDU-5G-75/SS

- Working capacity: 5 gal
- Inner shell diameter: 12"
- Pocket jacket dia.: 13 1/2"
- Straight sect. depth: 11"
- Bottom clearance: 14"

Model TFDU-2G-75/SS

- Working capacity: 2 gal
- Inner shell diameter: 8"
- Pocket jacket dia.: 9 1/2"
- Straight sect. depth: 8 1/2"
- Bottom clearance: 14"

Model TFDU-1G-75/SS

- Working capacity: 1 gal (4 qt)
- Inner shell diameter: 6 1/2"
- Pocket jacket dia.: 8"
- Straight sect. depth: 7"
- Bottom clearance: 10"

Model TFDU-1/2G-75/SS

- Working capacity: 1/2 gal (2 qt)
- Inner shell diameter: 5"
- Pocket jacket dia.: 6 1/2"
- Straight sect. depth: 6"
- Bottom clearance: 10"



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>