



**KETTLE, PROCESS, SANITARY  
F&D BOTTOM,  
HEATING & COOLING,  
SIDE & F&D JACKET, 75 PSIG**

**MODEL TFDU-25L-100J-SS316**

25 liter, working capacity  
30 liter, maximum capacity

**Features:**

- Materials: SS 316L
- Inner shell diameter:12"
- Outer shell diameter:15"
- Straight section:12"
- Bottom, Flanged & dished (F&D)
- Jacket inlet & outlet: 1" ID & 5" long, ferrules.
- Drain: 1" ID & 5" long, ferrule
- Cover with 6 inlet ferrules held in place by 12" diameter sanitary clamp.
- Baffles, internal, 4 req'd, bolted and removable
- Mounting lugs, 3 req'd, 3 3/8" long.
- Inside finish, 150 grits, sanitary
- Outside finish, 120 grit



**Other components available:**

- Mixers, dispersers, air or electric
- Thermo probe and temperature display
- High speed blade , low speed turbine



DANTCO MIXERS CORPORATION  
9 OAK STREET  
PATERSON, NJ 07501-3013  
973-278-8776, FAX 973-278-1538  
EMAIL [sales@dantco.com](mailto:sales@dantco.com), WEB <http://www.dantco.com>