



**KETTLE, PROCESS,  
SANITARY  
CONE BOTTOM,  
HEATING/COOLING,  
SIDE & CONE JACKET,  
75 PSIG**

**MODEL TFDU-1G-2J-75/SS**

1 GALLON WORKING CAPACITY

- Materials SS304
- Inner shell dia. 6 1/2"
- Pocket jacket OD 8"
- Bottom cone 2 1/2"
- Jacket inlet/outlet 3/8" FNPT
- Baffles, 4 req'd 3/8" 10 ga.
- Drain ferrule, san. 1/2"
- Drain clearance 6"
- Top recess for cover 1/8"
- Cover, vacuum, "O" ring, 2 clamps 1/4"
- Cover center hole 3/4" ID & lip seal
- Thermowell 6" long
- Legs, 4 req'd 1 1/2" tubing
- Leg pads, 3'x3" 10 ga
- Finish, inside 240 grits
- Finish, outside 150 grits

Other components available:

- Mixers, air or electric motors
- Thermo Probe and temperature display

Application:

- Lab mill, low speed mixers, high speed dispersers.



DANTCO MIXERS CORPORATION  
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>