



**SERIES 3040  
MIXER, BRIDGE MOUNTED,  
THROUGH THE ROOF,  
FIXED SPEED**

**MODEL DRAM-C-300B-60C-SS**

Motor Data: 30 HP, 1750 rpm,  
230/460V, 3-phase,  
Expl. Proof

Drive: Falk Right Angle  
Mixer Reducer  
45 HP Thermal

Mixer Shaft  
Speed: 100 rpm, nominal

Outboard Bearing: 3 ½ ID, Thrust

Mixing Shaft: 3 ½ dia. SS304

Turbine, Mid: 42" dia, Type AFF

Turbine, Bottom: 56" dia, Type VHE

Bridge: 8" WF 30# Posts,  
10" WF 30# Horiz.

Roof Seal: Flashing &  
Counter-Flashing

Tank (In Place): 6K Gallon, SS304  
Heated, Insulated,  
Insulation Skin

Site Installation and Validation (as shown)

The motor reducer mounted outside for silent  
operation.

The bridge supports all loads.



DANTCO MIXERS CORPORATION  
9 OAK STREET  
PATERSON, NJ 07501-3013  
973-278-8776, FAX 973-278-1538  
EMAIL [sales@dantco.com](mailto:sales@dantco.com), WEB <http://www.dantco.com>