



**SERIES 3084
MIXER ASSEMBLY FOR BLENDING
HEAVY DUTY, FIXED SPEED,
IN LINE GEAR, BELT DRIVE**

MODEL SFG-C-150-1.4K-CS

Application: tinting, let down, water base
Density: 10.5 lbs/gal Viscosity: 90 to 130 KU
Square tank capacity: 1400 gallon

STANDARD FEATURES:

- 15 HP, 1750 rpm, expl. proof, 3/60/230/460V
- reducer, in line, through bore
- belt drive gear to motor
- mixing shaft speed 78 rpm
- mixing shaft diameter, 3"
- top & mid turbine, 32" diameter, type AFF, 4 pitched blades, axial down flow
- bottom turbine, 38" diameter, type AFF, 6 blades, axial flow up
- turbine tip speed 800 fpm, nominal
- mounting bridge, structural, carbon steel
- all wetted parts carbon steel

SPECIAL FEATURES (NOT SHOWN)

- Square tank, 6 foot square x 7 foot high, carbon steel, cone bottom, on 4 legs, closed top with hinged covers & fittings
- Tank maximum capacity 1400 gallon
- Electrical controls (starter with heaters, on/off switch).

These models with square tanks are most efficient in tinting, let down oil based or water based paints and coatings.



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013
973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>