



SERIES 2010

**DISPERSER, POST MOUNTED,
VARIABLE HIGH SPEED,
HIGH TORQUE,
MECHANICAL DRIVE**

MODEL DVH-150-48/26-STAR-TEFC/SS

Standard Features:

- Motor, 15 HP, 1750 rpm, 3-phase, 60 Hz, 230V, TEFC (non explosion proof), high efficiency
- Fixed center single belt drive, easy to change belt
- Mixing shaft (SS304), polished, speed range 650 to 3000 rpm, nominal
- Air-over-oil lift, 54" rise, with lift controls (3-way air valve, muffler, air pressure relief valve, foot valve), non foaming hydraulic oil
- High speed blade, high shear, type HSF-10 (10" dia.), 8" from floor
- Side mounted speed control with hand wheel
- Speed indicator (approximate speed)
- Manual head lock with torque arm
- Height limitation safety limit switch, non explosion proof (wired in series with on/off push button)
- Can lock, adjustable, up to 200 gallon change can
- Can lock limit switch, wired in series with on/off push button
- Motor starter, with heaters, reset button, on/off button
- Ammeter in NEMA 4 enclosure

This disperser has all the standard features needed for safe, efficient, and economic operation.

This unit is ready to be plugged in 230 volt outlet, non explosion proof.



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>