



## SERIES 507

LAB/PILOT DISPERSER VARIABLE HIGH SPEED DC MOTOR & SCR CONTROLLER

## MODEL: DDC-200-18/7-TEFC/SS

Special Features, as shown:

- 2 HP motor, TEFC
- In-Power: 10A, 220V, 60 Hz, single phase
- ON/OFF, RUN/JUG, Speed Pot
- Mixing shaft speed range: 100 to 1750 rpm
- Blade: 4" HSF style, high shear
- Lift, manual, hydraulic jack
- Can Lock, Chain, Binder, adjustable
- Plate Stand, Retort Bar (optional)
- Suitable for bench top operation, 5 gallon pail shown

## Options (not shown):

- Digital tachometer
- Pneumatic Lift & Controls, 18" rise, 6" throat
- Filter-Lubricator-Regulator
- Chuck, <sup>3</sup>/<sub>4</sub>", at mixing shaft

These units may be available in post mounted configuration in sizes up to 5 HP (non explosion proof).

Input power to units with ½ HP and 1 HP motors may be single phase, either 110V or 220V. Input power to units with 1½ HP motors and up is single phase, 220V.

Price list shows price of units with standard features and options for special units.

All motors are available with top speed of either 1750 rpm or 2500 rpm,

