



**SERIES 5004  
AIR MIXER/DISPENSER  
TANK LID/BRIDGE MOUNTED**

**MODEL DAL-150-PLB-22**

- Variable speed
- Heavy duty
- Standard torque
- Mixing/Dispensing applications

**Standard Features:**

- 1 ½ hp @ top speed
- 100 to 3000 rpm, nominal
- 7/8" mixing shaft, SS304
- 4" high shear (type HSF) blade
- Needle valve for speed control
- Silencer at air exhaust
- Cover, 21" diameter, hinged, SS304
- Bridge, fabricated channel, SS304
- Mixer bracket, bolted, SS304
- Handles, 2 required, SS304
- Mixing shaft inclination, 10 degrees
- Weight, 35 lbs (easy to lift & move)

**Optional Accessories:**

- Filter regulator lubricator (FRL), and pressure gage (recommended)
- Blades with hub
- 3/8" air line and connections
- Choice of cover sizes
- Mixing vessels, cone bottom, with heating/cooling jacket
- Marine type propellers

The filter regulator lubricator (FRL) with gage is offered as an option. However, it is recommended for long and reliable air motor operation. One FRL may serve several mixers. Air requirement is 70 cfm



**DANTCO MIXERS CORPORATION**  
9 OAK STREET  
PATERSON, NJ 07501-3013  
973-278-8776, FAX 973-278-1538  
EMAIL [sales@dantco.com](mailto:sales@dantco.com), WEB <http://www.dantco.com>