



**SERIES 501
MODEL AM-150-P-5C/30C-10/6
LAB AIR MIXER**

- Variable high speed
- Heavy duty
- Standard torque
- Explosion proof (intrinsic)
- Mixing/Dispersing application

STANDARD FEATURES, BASIC:

- 1½ HP at top speed
- Variable speed, 500 to 3000 rpm, nominal
- ¾" diameter, 10" long, SS mixing shaft,
- 1" and 2" HSF high shear SS blade
- Lift on 1" diameter rod, 34" high
- Throat, 6 ½"
- Needle valve for speed control
- Silencer at exhaust
- Hollow shaft and 2 set screws
- Plate stand, carbon steel

OPTIONAL ACCESSORIES:

- Can lock assembly with chain
- Tachometer, analog or digital
- Filter/regulator/lubricator (FRL)
- 3/8" air line and quick disconnects
- Model PP mixing pails, 1/2 gallon, 1 gal., 2 gal., 3 gal., 5 gal. capacity, sanitary finish
- Model TFDU, mixing pails/kettles, ½ gallon, 1 gal., 2 gal., 3 gal., and 5 gal. capacity, sanitary finish



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>