

SERIES 3021 MIXER ASSEBLY FOR BLENDING HEAVY DUTY, FIXED SPEED

MODEL FSB-OB-100-130-2T-SS

Application: mixing stored products (fragrance oils)

STANDARD FEATURES:

- 10 HP, 1750 rpm, expl. proof, 3/60/230/460V
- reducer, in line, through bore
- mixing shaft speed 125 rpm
- mixing shaft diameter, 1 1/2"
- mid turbine, 28" diameter, type AFF, 4 pitched blades, 1/4" x 2", axial down flow
- bottom turbine, 28" diameter, type AFF-S, 4 pitched blades, 1/4" x 2", stabilizer, axial flow down
- turbine tip speed 900 fpm, nominal
- mixing shaft seal, packing gland, 5 psig
- mounting flange, 8" ANSI, carbon steel clad with SS
- wetted parts, stainless steel, type 304

SPECIAL FEATURES (NOT SHOWN)

- Storage Tank, Vertical, Model TVFD-3.1K-SS, with 4 baffles, F&D flanges top & bottom, top manhole & fittings, on 4 legs
- Electrical controls (starter with heaters & on/off switch).

These models may be supplied with very high efficiency turbine (type VHE) at the bottom requiring far less power to achieve optimum mixing.

DANTCO MIXERS CORPORATION 9 OAK STREET PATERSON, NJ 07501-3013 973-278-8776, FAX 973-278-1538 EMAIL sales@dantco.com, WEB http://www.dantco.com



DANTCO MIXERS CORPORATION 9 OAK STREET PATERSON, NJ 07501-3013 973-278-8776, FAX 973-278-1538 EMAIL sales@dantco.com, WEB http://www.dantco.com