



AIR MIXER/DISPERSER, KETTLE, TEMPERATURE DISPLAY SYSTEM

MODEL 501A5GTDSYS

Standard Features:

Air Mixer/Dispenser:

- Air motor, 1 HP at 90 psig & 3000 rpm
- Variable speed, 100 to 3000 rpm
- Speed control valve and muffler
- Mixing shaft with 2" type HSF blade
- Bolted bracket, bent at 15 degrees

Heating/Cooling Kettle:

- Kettle, 5 gallon working capacity
- 30 degrees cone
- Side jacket, 75 psig, heating cooling
- Top recessed and hinged cover
- Cover with slot for shaft entering with Teflon shoe
- Sanitary drain, 1"
- Sanitary finish
- Support, 4 legs, tubing, 12" from drain
- Leg pads

Thermo Probe & Digital Display:

- Side mounted Thermo Probe
- Temperature digital display with 120V cord
- Display encased in stainless box and bolted to welded bracket

Materials & Finish:

- Materials: SS304
- Inside finish 150 grit
- Outside finish 150 grits

APPLICATION:

- Lab mill
- Mixers, Low Speed
- Dispersers, High Speed



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>