



LAB/PILOT AIR MIXER/KETTLE SYSTEM

MODEL AMK-150SAR-TCOU-20/75SS

Standard Features:

Air Mixer/Dispenser:

- Air motor, 1 1/2 HP at 90 psig & 3000 rpm
- Gear reducer, 60:1 ratio
- Variable speed, 0 to 50 rpm, nominal
- Speed control needle valve and muffler
- Mixing shaft, sweeping anchor turbine (SAT), center mounted
- Outboard bearing

Heating/Cooling Kettle:

- Kettle, 20 gallon working capacity
- 45 degrees cone bottom
- Side/cone jacket, 75 psig, heating cooling
- Jacket inlet & outlet, 3/8" FNPT
- Top recessed and hinged cover
- Sanitary drain, 1 1/2" ferrule
- Sanitary finish
- Support, 4 legs, tubing, 12" from drain
- Leg pads
- SS casters with brakes & plastic wheels

Materials & Finish:

- Materials: SS304
- Inside finish 150 grit
- Outside finish 150 grits

APPLICATION:

- Mixing/blending, Low Speed
- High Viscosity Product Processing



DANTCO MIXERS CORPORATION
9 OAK STREET
PATERSON, NJ 07501-3013
973-278-8776, FAX 973-278-1538
EMAIL sales@dantco.com, WEB <http://www.dantco.com>